


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		DESIGNED PER HELI PRODUCTS TOOLS.	9/28/2009	WP	DW
1A		ADDED NOTE 2 TO USE PERMATEx THREAD SEALANT PER D.W.	5/9/2012	RJC	DW
1B		-01 CH'D GAUGE WAS PACIFIC RUBBER #W1K9692040 IS PARAMOUNT SUPPLY #ASHCROFT 1008.	3/24/2014	RJC	RW
1C	14-0213	CH'D TITLEBLOCK WAS RED BARN IS DART. RE-DRAWN IN SOLIDWORKS. ADDED ENGRAVE T/N NOTE. -01 CH'D B/O INFO WAS #ASHCROFT 1008 IS #63-1008-S-02L-300#-XLL.	11/12/2014	DPD	JAG
2	16-0145	-01 CH'D B/O REF WAS PARAMOUNT SUPPLY #63-1008-S-02L-300#-XLL IS MCMASTER-CARR #4053K751.	9/12/2016	DPD	JAG



#### NOTES:

1. FUNCTION: USED TO TEST AND REFILL ACCUMULATORS.
2. ASSEMBLE USING PERMATEx THREAD SEALANT OR EQUIVALENT.
3. ALSO IN KIT RBEA62309.

<b>DART AEROSPACE</b>	
TITLE <b>HYD. ACCUM. FITTING GAUGE</b>	
DWG NO. <b>RBE-350HYD</b>	REV <b>2</b>
MAT'L REAT TREAT FINISH SPEC	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125°	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY:	PERRITT
CHECKED:	MACKOVJAK
OPPS APPR:	ANDERSON
QA APPR:	LINDSAY
APPROVED:	GILBERT
EUROCOPTER AS350/355	
SCALE	1:2
DATE	9/9/2009
SHEET 1 OF 1	

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
		B/O	-01	1	PRESSURE GAUGE, 0-300 PSI		0-300 psi (0-2,000 kPa) (MCMASTER-CARR #4053K751)	1
		B/O	-03	1	1/4 NPT FEMALE "T" FITTING	BRASS	(PACIFIC RUBBER #PAR2203P-4)	1
		B/O	-05	1	1/4 NPT TO 1/8 NPT REDUCER FITTING	BRASS	(PACIFIC RUBBER #PAR209-4-2)	1
		B/O	-07	1	SCHRADER VALVE	S.S.	(PACIFIC RUBBER #AMF556)	1
		B/O	-09	1	1/4 NPT SQUARE PLUG	BRASS	(PACIFIC RUBBER #PAR211P-4)	1